

BIADESIVO RETINATO

TECHNICAL DATA SHEET	
CARRIER	Reinforced transfer
ADHESIVE SYSTEM	Water based acrylic
RELEASE LINER	Yellow paper
DESCRIPTION	
It has very good initial tack with very high peel adhesion to a wide variety of low surface energy substrates such as foams, PE, PP and EPDM. Ideal for lamination adhesive for a wide variety of laminates.	

METHOD		UNIT	TYPICAL VALUE
Carrier + adhesive thickness	AFERA 5006	Microns μ	80
Liner thickness	AFERA 5006	Microns μ	90
Peel Adhesion	AFERA 5001	N/25 mm	18
Temperature resistance			- 40 °C + 90 °C

SAFETY AND DISPOSAL INFORMATION	
<input type="checkbox"/> The adhesive does not contain heavy metal, formaldehyde and aromatic amines	<input type="checkbox"/> Catalogued as " Not Hazardous Special Industrial Waste"

NOTE
<p>To apply the self adhesive tape it is necessary that the surface is clean and dry.</p> <p>To maintain the product functionality the tape must be kept in their original packaging, the temperature must be between 15 and 22 C°, the humidity level below 65%. Do not expose the product to direct light and heat source. In this condition the product maintains their characteristics for 12 months.</p> <p>The values of this technical datasheet are based on our test we believe to be reliable and correct, nevertheless, they cannot represent any form of warranty ,either expressed or applied.</p> <p>User shall rely on his own information and tests to determine suitability of the product for the intended use, and the user assumes all risk and liability resulting from the use of this product. Do not hesitate to contact us for any question.</p>

The technical data are based from the original values of the manufacturer on tests performed on the standard production.